



TITLE 24 DEFAULT VALUES (U-FACTOR & SHGC)

SINGLE LITE or SDL w/ airspace greater than or equal to 7/16"	Fixed	Single Glazed	Clear	U-Factor = 1.04 SHGC = 0.76
			Tinted	U-Factor = 1.04 SHGC = 0.63
		Dual Glazed	Clear	U-Factor = 0.55 SHGC = 0.67
			Tinted	U-Factor = 0.55 SHGC = 0.55
	Operable	Single Glazed	Clear	U-Factor = 0.99 SHGC = 0.74
			Tinted	U-Factor = 0.99 SHGC = 0.60
		Dual Glazed	Clear	U-Factor = 0.58 SHGC = 0.65
			Tinted	U-Factor = 0.58 SHGC = 0.53
	Door	Single Glazed	Clear	U-Factor = 0.99 SHGC = 0.74
			Tinted	U-Factor = 0.99 SHGC = 0.60
		Dual Glazed	Clear	U-Factor = 0.53 SHGC = 0.65
			Tinted	U-Factor = 0.53 SHGC = 0.53

TDL or SDL w/ airspace less than 7/16"	Fixed	Single Glazed	Clear	U-Factor = 1.09 SHGC = 0.76
			Tinted	U-Factor = 1.09 SHGC = 0.63
		Dual Glazed	Clear	U-Factor = 0.60 SHGC = 0.67
			Tinted	U-Factor = 0.60 SHGC = 0.55
	Operable	Single Glazed	Clear	U-Factor = 1.04 SHGC = 0.74
			Tinted	U-Factor = 1.04 SHGC = 0.60
		Dual Glazed	Clear	U-Factor = 0.63 SHGC = 0.65
			Tinted	U-Factor = 0.63 SHGC = 0.53
	Door	Single Glazed	Clear	U-Factor = 1.04 SHGC = 0.74
			Tinted	U-Factor = 1.04 SHGC = 0.60
		Dual Glazed	Clear	U-Factor = 0.58 SHGC = 0.65
			Tinted	U-Factor = 0.58 SHGC = 0.53